

## BACKGROUND OF THE INVENTION

Sub  
All

[0001] The present invention relates to an information transacting and updating mechanism between remote parties, especially an information transacting and updating mechanism utilizes decomposing and packing techniques for speeding transfer and update of data between the remote parties.

SW AB

[0002] In the internet era, data sharing is important in different applications such as the on-line game, the net conference, and the supply chain because users of the above applications need to know the updated data from others as soon as possible. Conventionally, the updated data of a first party needs to be transferred to a second party for immediate reference. Similarly, the updated data of the second party may have to be transferred to the first party for immediate reference. For transferring updated data between two parties, a large amount of images, data frames, and data have to be transferred and duplicated between the two parties.



box is modified from the original information box by the customer and then sent to the provider via e-mail. A second transacted information box is modified from the first transacted information box by the provider and then sent to the customer via e-mail.

Sub  
A4

[0006] Another aspect of the present invention is to provide an information transacting mechanism between an information provider and a customer. The information transacting mechanism comprises an information server controlled by the information provider. An original information box is extracted from the information server. A tool server is installed with a plurality of tools by an application service provider and provides tools when instructed by the application service provider. A tool-added information box is resulted by packing the original information box with tools of the tool server and sent to the customer for the customer to access the data contained in the tool-added information box.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0007] Fig. 1A is a schematic view in accordance with the present invention showing a relational database being decomposed into several partitions;

[0008] Fig. 1B is a schematic view in accordance with the present





customized data, the provider 1 may correspondingly "answer" questions of the customer. When the customer receives the original information box 11, he/she can input specific data to replace corresponding original data without changing the format of the original information box 11. The specific data inputted by the customer 14 are called modified portion hereinafter. Therefore, a first transacted information box 12 is modified from the original information box 11 by the customer 14 according to his/her specific needs and then sent to the provider 1 via e-mail. A second transacted information box 13 is modified from the first transacted information box 12 by the provider 1 and then sent to the customer 14 by e-mail. The provider 1 provides the requested information in the second transacted information box 13 to the customer 14 according to the modified portion inputted by the customer 14 thereby answering the customer's requirement.

*sub AC* [0017] Referring to Fig. 3, the original information box 11 contains many data sections 22, for example, DATA SECTION 1, DATA SECTION 2, and DATA SECTION 3, and each data section 22 is associated with an identification tag 21, for example, TAG 1, TAGE 2, and TAG 3. These tags 21 are logic flags which indicate whether the corresponding data sections 22 have been rewritten.

[0018] The provider 1 will know the modified portions based on the identification tags 21, upon receipt of the first transacted information box 12. The provider 1 will modify the data stored in the first transacted information box 12 according to the modified data inputted by the customer 14. Therefore, answers inputted by the provider 1 corresponding to the inputted data by the customer 14 are together finalized in the second transacted information box 13 and shared by the provider 1 and the customer 14. With this mechanism, an interactive database updating can be performed between the provider 1 and the customer 14.

*Sub A7* [0019] A second embodiment is modified from the first embodiment and shown in Fig. 4. The mechanism comprises an information server 31 which is controlled by an information provider. An original information box 33 is extracted from the information server 31 which only contains data while not contains necessary tools to access the data. The original information box 33 is packed with tools by a tool server 34 owned by an application service provider and changed to be a tool-added information box 35 and sent to a customer 36 via e-mail from the application service provider. Specifically, the tool server 34 may pack different tools into the original information box 33 based on instructions

from the application service provider. For example, the tool server 34 may comprise a read tool, a delete tool, a write tool and an authority setting tool. The read tool allows the customer 36 to read the information contained in the original information box 33. The delete tool allows the customer 36 to delete information contained in the original information box 33. The write tool allows the customer 36 to modify the information contained in the original information box 33. The authority setting tool allows the customer 36 to set authority levels for a subsequent customer (not shown) to either read-only or modify the data contained in the tool-added information box 35 passed by the previous customer 36.

Sub A.8.1 [0020] A transacted information box 37 is resulted after the customer 36 has modified the data contained in the tool-added information box 35. The transacted information box 37 is then sent back to the information server 31 for updating via e-mail. The information server 31 has the right to determine whether to accept the update or not. This updating mode is called a copied mode.

Sub A9 [0021] Referred to Fig. 5, a third embodiment of the mechanism is used in a web site and modified from the second embodiment. The mechanism comprises an information server 41 controlled by an information provider (not shown). Different original information boxes



43 are extracted from the information server 41 and each specific original information box 43 only contains data while not contains necessary tools to access the data. Each original information box 43 contains specific information according to predetermination of the information provider. Each original information box 43 is packed with tools by a tool server 44 owned by an application service provider and changed to be a tool-added information box 45 and sent to a web server 46 via internet. Different customers 47 may visit a web page (not shown) associated with the web server 46 thereby selectively obtaining the tool-added information box 45 meeting respective needs. The customers 47 can modify the data based on the tools provided in the information box 45 and the transacted data in each information box 45 may be sent back to the information server 41 for updating.

[0022] In this embodiment, there are two modes for updating the data of the information server 41. The first mode is called a master-slave mode by which the information server 41 will be automatically updated whenever it detects and receives the transacted data. The second mode is called a replication mode by which the transacted data performed by different customers are put into a queue first and then update the information server 41 sequentially.

